

Symmetrical




Pole-top luminaires with symmetrical light distribution with LED or for fluorescent lamps

- Protection class IP 65
- Cast aluminium, aluminium and stainless steel
- Synthetic cover with white, light-diffusing matt finish
- Luminaires with LED · dimmable 1-10V
- Accessories for power reduction of LED luminaires with 1-10V interface can be found on Page 513.
- Luminaires for fluorescent lamps with electronic ballast
- You can find luminaires for operating with alternating and direct current in the table under AC/DC.


In the table we recommend BEGA luminaire poles whose surface quality and colour as well as design and statics match the luminaires on this double page. You can find the complete overview as well as the technical data of all BEGA luminaire poles, anchorage units and connection boxes on Pages 506 to 513.

- LED colour temperature optionally 4000K or 3000K
- 4000K – Article number
- 3000K – Article number + **K3**
- Luminaire colour optionally graphite or silver
- Graphite – Article number
- Silver – Article number + **A**



Pole-top luminaires · Fig. left

	Lamp	Base	Lumen	A	B	AC/DC
8260	LED 26.4 W	—	2300	700	320	✓
8367	2 TC-L 24 W	2 G11	3600	700	320	✓
8369	3 TC-L 36 W	2 G11	8700	700	320	✓



Pole-top luminaires · Fig. right

	Lamp	Base	Lumen	A	B	AC/DC
8100	LED 26.4 W	—	2300	615	130	✓
8155	2 TC-L 24 W	2 G11	3600	615	130	✓
8156	3 TC-L 24 W	2 G11	5400	615	130	✓

Luminaire poles

Height	Top	Pole	Group	Pole	Group
4000 - 6000	Ø76	914·915·916	34	791·794	14
4000 - 5000	Ø76	914·915	34	791·794	14
4000 - 6000	Ø76	914·915·916	34	792·794	14

Luminaire poles

Height	Top	Pole	Group	Pole	Group
4000 - 6000	Ø76	914·915·916	34	791·794	14
4000 - 5000	Ø76	914·915	34	791·794	14
4000 - 6000	Ø76	914·915·916	34	792·794	14

